


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm		
NAME: CW	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 86.32 lm/W
MODEL	2835L-24V-G02-2765	I _{max} (cd)	249.1	S/MH (C0/180)	1.30	
NOMINAL POWER (W)		LOR (%)	100.0	S/MH (C90/270)	1.28	
RATED VOLTAGE (V)	24	TOTAL FLUX (lm)	768.31	η UP, DN (C0-180)	0.0, 51.2	
NOMINAL FLUX (lm)	768.313	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 48.8	
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.50	
TEST VOLTAGE (V)	24	η down (%)	100.0	CIBSE SHR MAX	1.50	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2018-08-15

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 9.690m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C90	C180	C270					γ	Φ zone	Φ total	%lum, lamp
10	246.4	247.1	245.4	244.4					0- 10	23.62	23.62	3.07,3.07
20	237.0	238.2	235.1	232.9					10- 20	68.27	91.89	12,12
30	220.4	222.3	217.9	214.5					20- 30	105.2	197.1	25.7,25.7
40	196.3	199.0	193.6	189.1					30- 40	129.9	327.0	42.6,42.6
50	164.4	168.2	162.2	153.9					40- 50	138.2	465.2	60.5,60.5
60	125.0	129.8	123.7	115.1					50- 60	128.3	593.5	77.2,77.2
70	79.12	85.23	79.25	70.47					60- 70	100.3	693.8	90.3,90.3
80	31.60	38.73	33.14	26.59					70- 80	58.14	751.9	97.9,97.9
90	0.9569	4.972	1.454	2.870					80- 90	16.38	768.3	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 396.23 lm

%lum = 51.6%

%lamp = 51.6%

Conical surface Flux(120deg): 593.46 lm

%lum = 77.2%


%lamp = 77.2%

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2018-08-15

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:9.690m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm		
NAME: CW	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1130	1723
80	1449	1776
75	1687	1895
70	1841	1984
65	1935	2038
60	1990	2067
55	2022	2081
50	2037	2083
45	2042	2077


C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2018-08-15

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 9.690m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm		
NAME: CW	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.03	.99	.95	1.01	.97	.93	.97	.94	.90	.93	.90	.88	.89	.87	.85	.83
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.81	.76	.72	.78	.74	.71	.68
3.0	.78	.70	.63	.77	.69	.63	.74	.67	.62	.71	.65	.61	.68	.64	.59	.57
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.63	.57	.51	.61	.55	.51	.49
5.0	.62	.52	.46	.61	.52	.45	.58	.51	.45	.56	.50	.44	.55	.49	.44	.42
6.0	.55	.46	.40	.54	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2018-08-15

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 9.690m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm					
NAME: CW			TYPE:		WEIGHT:
SPEC.:			DIM.:		SERIAL No.:
MFR.:			SUR.:		Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.318	.181	.057	.311	.178	.056	.298	.171	.055	.286	.165	.053	.275	.159	.051		
2.0	.299	.164	.050	.292	.161	.050	.281	.156	.048	.270	.151	.047	.260	.147	.046		
3.0	.276	.147	.044	.270	.145	.044	.260	.141	.043	.250	.137	.042	.241	.134	.041		
4.0	.254	.132	.039	.249	.130	.039	.240	.127	.038	.231	.124	.037	.223	.121	.037		
5.0	.234	.119	.035	.230	.118	.034	.222	.115	.034	.214	.113	.034	.207	.111	.033		
6.0	.217	.109	.031	.213	.108	.031	.206	.105	.031	.199	.103	.030	.193	.101	.030		
7.0	.202	.100	.028	.198	.099	.028	.192	.097	.028	.186	.095	.028	.180	.093	.027		
8.0	.188	.092	.026	.185	.091	.026	.179	.090	.026	.174	.088	.025	.169	.087	.025		
9.0	.176	.085	.024	.173	.085	.024	.168	.083	.024	.163	.082	.023	.159	.081	.023		
10.0	.165	.079	.022	.163	.079	.022	.158	.078	.022	.154	.076	.022	.150	.075	.022		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.181	.156	.134	.155	.134	.115	.106	.092	.080	.061	.053	.046	.020	.017	.015	
2.0	.173	.132	.097	.148	.114	.084	.102	.079	.059	.059	.046	.034	.019	.015	.011	
3.0	.166	.114	.073	.142	.099	.064	.097	.069	.045	.056	.040	.026	.018	.013	.009	
4.0	.158	.101	.058	.136	.087	.050	.093	.061	.035	.054	.036	.021	.017	.012	.007	
5.0	.151	.091	.047	.129	.079	.041	.089	.055	.029	.052	.032	.017	.017	.011	.006	
6.0	.143	.082	.039	.123	.071	.034	.085	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.137	.076	.033	.117	.065	.029	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.130	.070	.028	.112	.060	.025	.077	.042	.018	.045	.025	.010	.015	.008	.003	
9.0	.124	.065	.025	.107	.056	.022	.074	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.118	.061	.022	.102	.053	.019	.071	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2018-08-15

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 9.690m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm										
NAME: CW					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.:					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	16.4	18.0	16.7	18.2	18.4	16.6	18.1	16.8	18.3	18.5
3H	18.0	19.5	18.3	19.7	19.9	18.2	19.7	18.5	19.9	20.2
4H	18.6	20.0	19.0	20.3	20.5	18.9	20.3	19.3	20.6	20.8
6H	19.1	20.3	19.4	20.6	20.9	19.5	20.8	19.8	21.0	21.3
8H	19.2	20.4	19.5	20.7	21.0	19.6	20.9	20.0	21.2	21.5
12H	19.2	20.4	19.6	20.7	21.0	19.8	21.0	20.1	21.3	21.6
4H 2H	17.1	18.5	17.4	18.7	19.0	17.2	18.6	17.5	18.8	19.1
3H	18.9	20.1	19.2	20.4	20.7	19.1	20.3	19.4	20.6	20.9
4H	19.6	20.7	20.0	21.0	21.4	19.9	21.0	20.3	21.3	21.6
6H	20.2	21.1	20.6	21.5	21.9	20.5	21.5	20.9	21.9	22.2
8H	20.3	21.2	20.7	21.6	22.0	20.8	21.7	21.2	22.1	22.4
12H	20.4	21.3	20.8	21.6	22.0	21.0	21.8	21.4	22.2	22.6
8H 4H	19.9	20.8	20.3	21.2	21.6	20.2	21.1	20.6	21.4	21.8
6H	20.6	21.4	21.1	21.8	22.2	21.0	21.7	21.4	22.1	22.6
8H	20.9	21.5	21.3	22.0	22.4	21.3	22.0	21.8	22.4	22.8
12H	21.0	21.6	21.5	22.1	22.5	21.6	22.2	22.1	22.6	23.1
12H 4H	19.9	20.8	20.4	21.2	21.6	20.2	21.0	20.6	21.4	21.8
6H	20.7	21.4	21.1	21.8	22.2	21.0	21.7	21.5	22.1	22.6
8H	21.0	21.6	21.5	22.0	22.5	21.4	22.0	21.9	22.4	22.9
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.4					+ 0.1 / - 0.3				

CIE Pub.117, 768.3 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.9)

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2018-08-15

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:9.690m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm		
NAME: CW	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	37	56	44	37	54	44	37	31
0.80	66	54	47	65	54	47	64	53	46	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	81	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	61
2.00	94	85	79	92	84	78	89	82	76	68
2.50	98	90	84	96	89	83	92	86	81	73
3.00	102	95	89	99	93	88	95	90	86	77
4.00	106	100	95	103	98	94	99	95	91	82
5.00	108	103	99	106	101	98	101	98	95	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators:
 Test Date: 2018-08-15

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 9.690m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm		
NAME: CW	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2018-08-15

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 9.690m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm		
NAME: CW	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:
Test Date:2018-08-15

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:9.690m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm		
NAME: CW	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2018-08-15

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 9.690m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.3709A P:8.900W PF:1.000 Freq:49.99Hz Lamp Flux:768.313x1 lm		
NAME: CW	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	1930
L_0~180 (75) av	1703
L_0~180 (85) av	1185
L_90~270 (65) av	1899
L_90~270 (75) av	1679
L_90~270 (85) av	1327
L_45 (65) av	1910
L_45 (75) av	1689
L_45 (85) av	1277

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:
 Test Date:2018-08-15

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:9.690m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators:
Test Date: 2018-08-15

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 9.690m [K=1.0000]
Remarks:

