


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz Lamp Flux:67.4015x1 lm		
NAME: 02 RGB+CCT B	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 14.47 lm/W			
MODEL		I <sub>max</sub> (cd)	20.95	S/MH(C0/180)	1.26
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.38
RATED VOLTAGE(V)		TOTAL FLUX(lm)	67.402	η UP,DN(C0-180)	0.3,46.7
NOMINAL FLUX(lm)	67.4015	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.5,52.5
LAMPS INSIDE	1	η up(%)	0.8	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)		η down(%)	99.2	CIBSE SHR MAX	1.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum, lamp
10	20.89	20.71	20.42	20.12	20.10	20.33	20.63	20.77	0- 10	1.965	1.965	2.92,2.92
20	20.75	20.28	19.59	19.06	19.05	19.58	20.18	20.49	10- 20	5.725	7.690	11.4,11.4
30	19.83	19.17	18.09	17.44	17.49	18.30	19.23	19.68	20- 30	8.929	16.62	24.7,24.7
40	18.09	17.21	15.96	15.18	15.35	16.52	17.69	18.18	30- 40	11.15	27.76	41.2,41.2
50	15.41	14.42	13.02	12.28	12.60	14.04	15.35	15.88	40- 50	11.99	39.75	59,59
60	11.93	10.72	9.409	8.815	9.284	10.94	12.36	12.68	50- 60	11.18	50.94	75.6,75.6
70	7.800	6.496	5.329	5.112	5.782	7.339	8.628	8.762	60- 70	8.773	59.71	88.6,88.6
80	3.583	2.528	1.703	1.937	2.677	3.721	4.668	4.651	70- 80	5.280	64.99	96.4,96.4
90	0.3378	0.1985	0.1217	0.1824	0.3335	0.9256	1.135	1.010	80- 90	1.860	66.85	99.2,99.2
100	0.0606	0.0608	0.0607	0.0453	0.0305	0.0608	0.0607	0.0605	90-100	0.2213	67.07	99.5,99.5
110	0.0457	0.0608	0.0607	0.0453	0.0305	0.0608	0.0607	0.0608	100-110	0.0685	67.14	99.6,99.6
120	0.0457	0.0456	0.0607	0.0453	0.0305	0.0608	0.0607	0.0756	110-120	0.0618	67.20	99.7,99.7
130	0.0457	0.0456	0.0607	0.0453	0.0305	0.0608	0.0607	0.0907	120-130	0.0561	67.26	99.8,99.8
140	0.0457	0.0456	0.0607	0.0453	0.0305	0.0608	0.0607	0.1058	130-140	0.0498	67.31	99.9,99.9
150	0.0457	0.0456	0.0607	0.0453	0.0305	0.0608	0.0607	0.1058	140-150	0.0405	67.35	99.9,99.9
160	0.0457	0.0608	0.0607	0.0453	0.0305	0.0608	0.0607	0.1058	150-160	0.0302	67.38	100,100
170	0.0457	0.0608	0.0607	0.0453	0.0305	0.0608	0.0607	0.1058	160-170	0.0187	67.40	100,100
180	0.0609	0.0608	0.0607	0.0453	0.0305	0.0608	0.0607	0.1058	170-180	0.0062	67.40	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 33.752 lm

%lum = 50.1%

%lamp = 50.1%

Conical surface Flux(120deg): 50.936 lm

%lum = 75.6%


%lamp = 75.6%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JINZHI  
 Test Date:2021-07-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
 Humidity:65.0%  
 Test Distance:9.660m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz Lamp Flux:67.4015x1 lm		
NAME: 02 RGB+CCT B	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JINZHI  
Test Date: 2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity: 65.0%  
Test Distance: 9.660m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz		
Lamp Flux:67.4015x1 lm		
NAME: 02 RGB+CCT B	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
p <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### WEC AND CCEC

Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz		
Lamp Flux:67.4015x1 lm		
NAME: 02 RGB+CCT B	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.327	.186	.059	.320	.182	.058	.306	.175	.056	.293	.169	.054	.281	.163	.053		
2.0	.304	.166	.051	.297	.164	.050	.285	.158	.049	.274	.154	.048	.263	.149	.047		
3.0	.279	.149	.045	.273	.146	.044	.263	.142	.043	.253	.138	.042	.243	.135	.042		
4.0	.256	.133	.039	.251	.132	.039	.242	.128	.038	.233	.125	.038	.224	.122	.037		
5.0	.236	.120	.035	.232	.119	.035	.223	.116	.034	.215	.114	.034	.208	.111	.033		
6.0	.219	.110	.031	.214	.108	.031	.207	.106	.031	.200	.104	.030	.193	.102	.030		
7.0	.203	.100	.028	.199	.099	.028	.192	.097	.028	.186	.095	.028	.180	.094	.027		
8.0	.189	.092	.026	.186	.092	.026	.180	.090	.026	.174	.088	.025	.169	.087	.025		
9.0	.177	.086	.024	.174	.085	.024	.169	.083	.024	.163	.082	.023	.158	.080	.023		
10.0	.166	.080	.022	.164	.079	.022	.159	.078	.022	.154	.076	.022	.149	.075	.022		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.197	.197	.197	.168	.168	.168	.115	.115	.115	.066	.066	.066	.021	.021	.021	
1.0	.188	.162	.139	.161	.139	.120	.110	.096	.083	.063	.055	.048	.020	.018	.016	
2.0	.180	.138	.103	.154	.119	.089	.106	.082	.062	.061	.048	.036	.020	.015	.012	
3.0	.173	.121	.079	.148	.104	.069	.102	.072	.048	.059	.042	.028	.019	.014	.009	
4.0	.165	.108	.064	.142	.093	.055	.097	.065	.039	.056	.038	.023	.018	.012	.008	
5.0	.158	.097	.053	.135	.084	.046	.093	.059	.032	.054	.035	.019	.017	.011	.006	
6.0	.150	.089	.045	.129	.077	.039	.089	.054	.028	.052	.032	.016	.017	.010	.005	
7.0	.143	.082	.039	.123	.071	.034	.085	.050	.024	.050	.029	.014	.016	.010	.005	
8.0	.137	.076	.035	.118	.066	.030	.082	.046	.021	.047	.027	.013	.015	.009	.004	
9.0	.131	.071	.031	.113	.062	.027	.078	.044	.019	.045	.026	.012	.015	.008	.004	
10.0	.125	.067	.029	.108	.058	.025	.075	.041	.018	.044	.024	.011	.014	.008	.004	

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

### UGR(Unified Glare Rating) Table

Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz										
Lamp Flux:67.4015x1 lm										
NAME: 02 RGB+CCT B					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.:					SUR.: 0.02*1			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	23.0	24.5	23.3	24.8	25.0	22.1	23.7	22.4	23.9	24.1
3H	24.7	26.1	25.0	26.3	26.6	23.4	24.9	23.7	25.1	25.4
4H	25.3	26.7	25.7	27.0	27.3	23.9	25.2	24.2	25.5	25.8
6H	25.9	27.2	26.2	27.5	27.8	24.1	25.4	24.4	25.7	26.0
8H	26.1	27.3	26.4	27.6	27.9	24.1	25.3	24.5	25.6	26.0
12H	26.2	27.4	26.6	27.7	28.0	24.1	25.3	24.5	25.6	25.9
4H 2H	23.5	24.9	23.8	25.1	25.4	22.8	24.2	23.2	24.5	24.8
3H	25.3	26.5	25.7	26.8	27.2	24.3	25.5	24.7	25.8	26.1
4H	26.1	27.2	26.5	27.6	27.9	24.8	25.9	25.2	26.3	26.6
6H	26.8	27.8	27.2	28.1	28.5	25.1	26.1	25.6	26.5	26.9
8H	27.0	28.0	27.5	28.3	28.7	25.2	26.1	25.6	26.5	26.9
12H	27.2	28.1	27.7	28.5	28.9	25.2	26.1	25.7	26.5	26.9
8H 4H	26.3	27.2	26.8	27.6	28.0	25.2	26.1	25.6	26.5	26.9
6H	27.1	27.9	27.6	28.3	28.7	25.6	26.3	26.0	26.8	27.2
8H	27.4	28.1	27.9	28.5	29.0	25.7	26.4	26.2	26.8	27.3
12H	27.7	28.3	28.2	28.7	29.2	25.7	26.3	26.2	26.8	27.3
12H 4H	26.3	27.1	26.7	27.5	28.0	25.2	26.0	25.6	26.4	26.8
6H	27.1	27.8	27.6	28.2	28.7	25.7	26.3	26.1	26.8	27.2
8H	27.5	28.1	28.0	28.5	29.0	25.8	26.4	26.3	26.8	27.3
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.1 / - 0.2					+ 0.2 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.3 / - 0.4				
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.4				

CIE Pub.117, 67.40 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -9.4)  
Area: 0.02 m2

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:


```

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

```

### ISOCANDELA DIAGRAM

Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz Lamp Flux:67.4015x1 lm		
NAME: 02 RGB+CCT B	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:



AAI Figure

Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz Lamp Flux:67.4015x1 lm		
NAME: 02 RGB+CCT B	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

ISOLUX DIAGRAM

Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz Lamp Flux:67.4015x1 lm		
NAME: 02 RGB+CCT B	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks:

## LED Avg.L Report

Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz Lamp Flux:67.4015x1 lm		
NAME: 02 RGB+CCT B	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	1035
L_0~180 (75) av	949
L_0~180 (85) av	878
L_90~270 (65) av	1062
L_90~270 (75) av	970
L_90~270 (85) av	939
L_45 (65) av	1053
L_45 (75) av	967
L_45 (85) av	950

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JINZHI  
 Test Date:2021-07-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
 Humidity:65.0%  
 Test Distance:9.660m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JINZHI  
Test Date: 2021-07-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity: 65.0%  
Test Distance: 9.660m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.000V I:0.1941A P:4.6584W PF:1.0000 Freq:0Hz																	
Lamp Flux:67.4015x1 lm																	
NAME: 02 RGB+CCT B									TYPE:						WEIGHT:		
SPEC.:									DIM.:						SERIAL No.:		
MFR.:									SUR.: 0.02*1						Shielding Angle:		

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7	20.7			
5	20.8	20.7	20.7	20.6	20.7	20.5	20.5	20.4	20.5	20.5	20.5	20.7	20.6	20.8	20.8	20.9			
10	20.9	20.6	20.7	20.4	20.4	20.2	20.1	20.1	20.1	20.3	20.3	20.6	20.6	20.8	20.8	20.9			
15	20.9	20.6	20.6	20.2	20.1	19.8	19.6	19.6	19.7	19.8	20.0	20.4	20.4	20.8	20.6	20.9			
20	20.8	20.3	20.3	19.8	19.6	19.2	19.1	19.0	19.0	19.3	19.6	20.0	20.2	20.6	20.5	20.8			
25	20.4	19.9	19.8	19.2	18.9	18.5	18.3	18.2	18.3	18.7	19.0	19.6	19.8	20.3	20.2	20.5			
30	19.8	19.3	19.2	18.5	18.1	17.6	17.4	17.4	17.5	17.9	18.3	18.9	19.2	19.8	19.7	20.0			
35	19.0	18.5	18.3	17.6	17.1	16.6	16.4	16.3	16.5	17.0	17.5	18.2	18.5	19.1	19.1	19.3			
40	18.1	17.5	17.2	16.5	16.0	15.4	15.2	15.1	15.3	15.9	16.5	17.2	17.7	18.2	18.2	18.4			
45	16.9	16.2	16.0	15.1	14.6	14.0	13.8	13.7	14.1	14.7	15.4	16.2	16.6	17.2	17.1	17.3			
50	15.4	14.7	14.4	13.6	13.0	12.4	12.3	12.3	12.6	13.3	14.0	14.9	15.3	15.9	15.9	15.9			
55	13.8	13.0	12.7	11.9	11.3	10.7	10.6	10.6	11.0	11.7	12.6	13.5	13.9	14.5	14.4	14.3			
60	11.9	11.2	10.7	9.92	9.41	8.89	8.82	8.86	9.28	10.1	10.9	11.9	12.4	12.8	12.7	12.5			
65	9.95	9.12	8.66	7.87	7.38	6.96	6.94	7.03	7.55	8.36	9.19	10.1	10.6	11.0	10.8	10.6			
70	7.80	7.03	6.50	5.78	5.33	5.00	5.11	5.28	5.78	6.59	7.34	8.22	8.63	9.03	8.76	8.51			
75	5.67	4.93	4.47	3.78	3.40	3.21	3.39	3.64	4.15	4.86	5.48	6.25	6.64	6.92	6.68	6.37			
80	3.58	2.90	2.53	1.93	1.70	1.59	1.94	2.16	2.68	3.26	3.72	4.36	4.67	4.88	4.65	4.25			
85	1.68	1.16	0.98	0.58	0.58	0.50	0.82	1.02	1.38	1.91	2.16	2.62	2.70	2.94	2.67	2.30			
90	0.34	0.23	0.20	0.05	0.12	0.06	0.18	0.21	0.33	0.83	0.93	1.22	1.14	1.26	1.01	0.81			
95	0.03	0.00	0.06	0.06	0.08	0.06	0.08	0.08	0.03	0.27	0.27	0.38	0.24	0.37	0.21	0.20			
100	0.06	0.05	0.06	0.06	0.06	0.06	0.05	0.08	0.03	0.11	0.06	0.14	0.06	0.14	0.06	0.09			
105	0.05	0.06	0.06	0.09	0.06	0.06	0.05	0.09	0.03	0.09	0.06	0.09	0.06	0.06	0.06	0.06			
110	0.05	0.06	0.06	0.09	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.08	0.06	0.06	0.06	0.06			
115	0.05	0.08	0.05	0.09	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.08	0.06	0.06	0.08	0.06			
120	0.05	0.08	0.05	0.09	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.08	0.06			
125	0.05	0.08	0.05	0.09	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.09	0.06			
130	0.05	0.08	0.05	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.09	0.06			
135	0.05	0.08	0.05	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			
140	0.05	0.08	0.05	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			
145	0.05	0.08	0.05	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			
150	0.05	0.08	0.05	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			
155	0.05	0.08	0.05	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			
160	0.05	0.09	0.06	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			
165	0.05	0.09	0.06	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			
170	0.05	0.06	0.06	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			
175	0.05	0.06	0.06	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			
180	0.06	0.06	0.06	0.11	0.06	0.06	0.05	0.09	0.03	0.06	0.06	0.06	0.06	0.06	0.11	0.06			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JINZHI  
Test Date:2021-07-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.446  
Humidity:65.0%  
Test Distance:9.660m [K=1.0000]  
Remarks: