


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 75.15 lm/W			
MODEL		Imax(cd)	75.29	S/MH(C0/180)	1.41
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.40
RATED VOLTAGE(V)		TOTAL FLUX(lm)	271.11	η UP,DN(C0-180)	0.4,48.4
NOMINAL FLUX(lm)	271.106	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.5,50.7
LAMPS INSIDE	1	η up(%)	0.9	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)		η down(%)	99.1	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	75.16	74.65	74.00	73.94	74.27	74.52	74.71	75.03	0- 10	7.136	7.136	2.63,2.63
20	74.42	73.33	72.18	72.25	72.99	73.00	73.14	74.13	10- 20	20.95	28.08	10.4,10.4
30	71.85	70.59	68.65	69.47	70.34	70.25	70.08	71.67	20- 30	33.25	61.33	22.6,22.6
40	67.38	65.63	63.07	64.73	65.41	65.49	65.19	67.38	30- 40	42.75	104.1	38.4,38.4
50	59.40	57.46	54.63	57.02	57.01	57.81	57.54	60.51	40- 50	47.85	151.9	56,56
60	47.03	45.47	42.84	45.20	44.88	46.62	46.68	49.59	50- 60	46.71	198.6	73.3,73.3
70	31.03	29.76	27.77	29.30	29.61	32.03	32.60	34.23	60- 70	38.22	236.9	87.4,87.4
80	13.46	13.00	12.22	12.51	13.09	16.05	16.95	16.61	70- 80	23.64	260.5	96.1,96.1
90	0.6339	2.209	2.433	1.871	0.9973	3.456	4.284	3.084	80- 90	8.165	268.7	99.1,99.1
100	0.1369	0.4875	0.7292	0.2885	0.1673	0.1974	0.4540	0.1667	90-100	1.062	269.7	99.5,99.5
110	0.1369	0.2280	0.2578	0.2274	0.2435	0.1366	0.2123	0.2274	100-110	0.2478	270.0	99.6,99.6
120	0.2280	0.2280	0.2275	0.2274	0.2890	0.2737	0.2730	0.3030	110-120	0.2318	270.2	99.7,99.7
130	0.2281	0.2432	0.2275	0.2274	0.3346	0.3191	0.3037	0.3183	120-130	0.2401	270.4	99.8,99.8
140	0.2433	0.2432	0.2428	0.2425	0.3346	0.3191	0.3185	0.3336	130-140	0.2198	270.7	99.8,99.8
150	0.2738	0.2583	0.2578	0.2728	0.3346	0.3191	0.3185	0.3490	140-150	0.1826	270.8	99.9,99.9
160	0.2738	0.2886	0.2730	0.2880	0.3346	0.3191	0.3185	0.3941	150-160	0.1395	271.0	100,100
170	0.2890	0.3039	0.3033	0.2880	0.3346	0.3191	0.3185	0.3941	160-170	0.0882	271.1	100,100
180	0.3194	0.3191	0.3185	0.3183	0.3346	0.3191	0.3185	0.3183	170-180	0.0304	271.1	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 127.72 lm

%lum = 47.1%

%lamp = 47.1%

Conical surface Flux(120deg): 198.64 lm

%lum = 73.3%


%lamp = 73.3%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	3276	3483
80	3870	3524
75	4295	3811
70	4529	4065
65	4651	4224
60	4695	4289
55	4680	4291
50	4613	4254
45	4512	4196


C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz		
Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JINZHI
 Test Date:2021-06-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
 Humidity:65.0%
 Test Distance:9.660m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.339	.193	.061	.331	.189	.060	.317	.182	.058	.304	.176	.056	.293	.170	.055		
2.0	.313	.172	.053	.307	.169	.052	.294	.164	.051	.283	.159	.050	.272	.154	.049		
3.0	.287	.153	.046	.281	.151	.045	.270	.146	.045	.260	.142	.044	.251	.139	.043		
4.0	.263	.137	.040	.258	.135	.040	.248	.131	.039	.239	.128	.039	.230	.125	.038		
5.0	.242	.123	.036	.237	.122	.035	.228	.119	.035	.220	.116	.035	.213	.114	.034		
6.0	.223	.112	.032	.219	.111	.032	.211	.108	.031	.204	.106	.031	.197	.104	.031		
7.0	.207	.102	.029	.203	.101	.029	.196	.099	.029	.189	.097	.028	.183	.095	.028		
8.0	.192	.094	.026	.189	.093	.026	.183	.091	.026	.177	.090	.026	.171	.088	.026		
9.0	.180	.087	.024	.177	.086	.024	.171	.085	.024	.166	.083	.024	.161	.082	.024		
10.0	.169	.081	.022	.166	.080	.022	.161	.079	.022	.156	.077	.022	.151	.076	.022		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.197	.197	.197	.169	.169	.169	.115	.115	.115	.066	.066	.066	.021	.021	.021	
1.0	.189	.163	.139	.162	.140	.120	.111	.096	.083	.064	.056	.048	.020	.018	.016	
2.0	.182	.139	.102	.156	.119	.088	.107	.083	.062	.062	.048	.036	.020	.016	.012	
3.0	.175	.121	.079	.150	.105	.068	.103	.073	.048	.059	.042	.028	.019	.014	.009	
4.0	.167	.108	.063	.144	.094	.055	.099	.065	.039	.057	.038	.023	.018	.012	.008	
5.0	.160	.098	.053	.137	.085	.046	.095	.059	.032	.055	.035	.019	.018	.011	.006	
6.0	.152	.090	.045	.131	.078	.039	.090	.054	.028	.052	.032	.016	.017	.010	.005	
7.0	.145	.083	.039	.125	.072	.034	.086	.050	.024	.050	.030	.014	.016	.010	.005	
8.0	.139	.077	.035	.119	.067	.030	.083	.047	.022	.048	.028	.013	.016	.009	.004	
9.0	.133	.072	.032	.114	.063	.028	.079	.044	.020	.046	.026	.012	.015	.009	.004	
10.0	.127	.068	.029	.109	.059	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz										
Lamp Flux:271.106x1 lm										
NAME: 10 RGBW G					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:		
MFR.:					SUR.: 0.02*1			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	23.0	24.5	23.2	24.8	25.0	22.6	24.1	22.8	24.4	24.6
3H	24.7	26.2	25.0	26.4	26.7	24.2	25.7	24.5	26.0	26.2
4H	25.4	26.8	25.8	27.1	27.4	24.9	26.3	25.2	26.6	26.8
6H	25.9	27.3	26.3	27.6	27.9	25.4	26.7	25.7	27.0	27.3
8H	26.1	27.4	26.4	27.7	28.0	25.5	26.8	25.9	27.1	27.4
12H	26.2	27.4	26.5	27.7	28.0	25.7	26.9	26.0	27.2	27.5
4H 2H	23.6	25.0	23.9	25.3	25.6	23.3	24.7	23.6	25.0	25.3
3H	25.5	26.8	25.9	27.1	27.4	25.1	26.4	25.5	26.7	27.0
4H	26.4	27.5	26.8	27.8	28.2	25.9	27.0	26.3	27.4	27.7
6H	27.0	28.0	27.4	28.4	28.8	26.5	27.5	26.9	27.9	28.3
8H	27.2	28.2	27.7	28.5	29.0	26.7	27.7	27.2	28.1	28.5
12H	27.4	28.2	27.8	28.6	29.1	26.9	27.8	27.4	28.2	28.6
8H 4H	26.7	27.6	27.1	28.0	28.4	26.2	27.2	26.7	27.6	28.0
6H	27.4	28.2	27.9	28.7	29.1	27.0	27.8	27.5	28.2	28.7
8H	27.7	28.4	28.2	28.9	29.4	27.3	28.0	27.8	28.5	29.0
12H	27.9	28.6	28.4	29.0	29.5	27.6	28.2	28.1	28.7	29.2
12H 4H	26.7	27.5	27.1	27.9	28.4	26.3	27.1	26.7	27.5	28.0
6H	27.5	28.2	28.0	28.6	29.1	27.1	27.8	27.6	28.2	28.7
8H	27.8	28.4	28.3	28.9	29.4	27.5	28.1	28.0	28.5	29.0
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4				

CIE Pub.117, 271.1 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -4.5)
Area: 0.02 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	54	42	34	53	41	34	52	41	34	27
0.80	64	52	44	63	51	44	61	50	43	36
1.00	72	61	53	71	60	52	69	62	52	44
1.25	80	68	61	78	68	60	75	66	59	52
1.50	85	74	67	83	73	66	80	71	65	57
2.00	92	83	76	90	82	75	87	79	74	65
2.50	97	88	81	94	87	80	90	84	79	70
3.00	100	93	87	98	91	85	94	88	83	74
4.00	105	98	93	102	96	92	98	93	89	79
5.00	107	102	97	105	100	96	100	96	93	83
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	4551
L_0~180 (75) av	4205
L_0~180 (85) av	3264
L_90~270 (65) av	4474
L_90~270 (75) av	4303
L_90~270 (85) av	4519
L_45 (65) av	4663
L_45 (75) av	4414
L_45 (85) av	4209

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JINZHI
Test Date: 2021-06-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity: 65.0%
Test Distance: 9.660m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.001V I:0.1503A P:3.6074W PF:1.0000 Freq:0Hz		
Lamp Flux:271.106x1 lm		
NAME: 10 RGBW G	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.: 0.02*1	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9	74.9			
5	75.1	74.9	75.0	74.7	74.6	74.5	74.5	74.6	74.7	74.8	74.8	75.0	74.9	75.1	75.1	75.2			
10	75.2	74.8	74.6	74.2	74.0	73.9	73.9	74.1	74.3	74.5	74.5	74.8	74.7	75.2	75.0	75.3			
15	75.0	74.4	74.1	73.5	73.2	73.0	73.1	73.4	73.7	73.9	73.9	74.2	74.1	74.7	74.7	75.2			
20	74.4	73.7	73.3	72.6	72.2	72.0	72.3	72.6	73.0	73.2	73.0	73.1	73.1	73.8	74.1	74.6			
25	73.4	72.6	72.2	71.2	70.6	70.5	71.0	71.5	71.9	72.2	71.8	71.7	71.8	72.7	73.1	73.7			
30	71.9	71.0	70.6	69.3	68.6	68.7	69.5	70.0	70.3	70.6	70.3	70.0	70.1	71.1	71.7	72.3			
35	69.9	69.0	68.4	66.9	66.3	66.4	67.4	67.9	68.2	68.5	68.2	67.7	67.9	69.1	69.8	70.5			
40	67.4	66.4	65.6	63.9	63.1	63.4	64.7	65.3	65.4	65.7	65.5	64.9	65.2	66.6	67.4	68.1			
45	63.9	63.1	62.0	60.2	59.3	59.8	61.3	61.7	61.6	62.1	62.0	61.5	61.7	63.3	64.4	64.9			
50	59.4	58.6	57.5	55.6	54.6	55.3	57.0	57.2	57.0	57.6	57.8	57.3	57.5	59.3	60.5	60.7			
55	53.8	53.1	52.0	50.2	49.2	49.9	51.7	51.6	51.4	52.2	52.7	52.2	52.5	54.3	55.6	55.3			
60	47.0	46.5	45.5	43.7	42.8	43.5	45.2	44.9	44.9	45.9	46.6	46.3	46.7	48.3	49.6	48.7			
65	39.4	38.8	38.0	36.4	35.7	36.2	37.6	37.4	37.6	38.6	39.7	39.5	40.0	41.3	42.4	41.1			
70	31.0	30.6	29.8	28.5	27.8	28.3	29.3	29.2	29.6	30.7	32.0	32.1	32.6	33.5	34.2	32.6			
75	22.3	22.0	21.2	20.3	19.7	20.2	20.7	20.7	21.3	22.4	24.0	24.2	24.8	25.3	25.5	23.7			
80	13.5	13.3	13.0	12.6	12.2	12.5	12.5	12.4	13.1	14.3	16.0	16.5	17.0	17.0	16.6	14.7			
85	5.72	5.46	5.96	6.07	6.06	6.23	5.96	5.36	5.66	7.27	8.83	9.57	9.69	9.47	8.61	6.80			
90	0.63	1.52	2.21	2.35	2.43	2.23	1.87	1.18	1.00	2.24	3.46	4.21	4.28	4.05	3.08	1.90			
95	0.14	0.39	1.07	1.17	1.28	0.88	0.55	0.20	0.14	0.41	0.85	1.45	1.51	1.51	0.82	0.32			
100	0.14	0.18	0.49	0.58	0.73	0.44	0.29	0.20	0.17	0.15	0.20	0.58	0.45	0.43	0.17	0.15			
105	0.14	0.23	0.23	0.23	0.36	0.24	0.24	0.23	0.21	0.15	0.20	0.23	0.20	0.20	0.18	0.15			
110	0.14	0.24	0.23	0.27	0.26	0.24	0.23	0.27	0.24	0.15	0.14	0.20	0.21	0.20	0.23	0.15			
115	0.21	0.29	0.23	0.27	0.23	0.29	0.23	0.29	0.27	0.17	0.24	0.20	0.24	0.20	0.24	0.20			
120	0.23	0.30	0.23	0.29	0.23	0.29	0.23	0.30	0.29	0.21	0.27	0.20	0.27	0.20	0.30	0.21			
125	0.23	0.32	0.23	0.30	0.23	0.32	0.23	0.32	0.32	0.21	0.32	0.21	0.29	0.21	0.29	0.23			
130	0.23	0.32	0.24	0.30	0.23	0.33	0.23	0.35	0.33	0.26	0.32	0.23	0.30	0.23	0.32	0.29			
135	0.23	0.32	0.24	0.30	0.23	0.33	0.24	0.35	0.33	0.24	0.32	0.23	0.32	0.23	0.33	0.29			
140	0.24	0.32	0.24	0.30	0.24	0.33	0.24	0.35	0.33	0.24	0.32	0.23	0.32	0.23	0.33	0.29			
145	0.26	0.32	0.24	0.30	0.24	0.33	0.27	0.35	0.33	0.26	0.32	0.24	0.32	0.23	0.35	0.29			
150	0.27	0.32	0.26	0.30	0.26	0.33	0.27	0.35	0.33	0.26	0.32	0.24	0.32	0.24	0.35	0.29			
155	0.27	0.32	0.27	0.30	0.27	0.33	0.27	0.35	0.33	0.27	0.32	0.27	0.32	0.26	0.38	0.29			
160	0.27	0.32	0.29	0.30	0.27	0.33	0.29	0.35	0.33	0.27	0.32	0.30	0.32	0.27	0.39	0.29			
165	0.29	0.32	0.32	0.30	0.29	0.33	0.29	0.35	0.33	0.27	0.32	0.29	0.32	0.27	0.39	0.29			
170	0.29	0.32	0.30	0.30	0.30	0.33	0.29	0.35	0.33	0.29	0.32	0.30	0.32	0.29	0.39	0.29			
175	0.30	0.32	0.30	0.30	0.32	0.33	0.30	0.35	0.33	0.30	0.32	0.30	0.32	0.32	0.39	0.30			
180	0.32	0.32	0.32	0.35	0.32	0.32	0.32	0.35	0.33	0.30	0.32	0.32	0.32	0.32	0.32	0.32			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JINZHI
Test Date:2021-06-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:9.660m [K=1.0000]
Remarks: